

# Big Blue®/Big Clear

## **CARTRIDGE HOUSINGS**

Big Blue® and Big Clear Filter Housings offer the versatility to meet larger capacity filtration needs. This reduces the number of housings required for high-flow applications.

#### **APPLICATIONS**

- Heavy Sediment Applications
- High-Flow Applications

### **FEATURES**

- Large capacity housing
- Sumps constructed of durable reinforced polypropylene
- Big Clear Filter Housings offer on-site examination of flow, performance and cartridge life
- 1.25-inch internal port to allow a greater volume of liquid to pass through the high-flow polypropylene cap more rapidly
- Accepts 4.5-inch diameter cartridges
- Compatible with a broad range of chemicals

#### **HOUSING OPTIONS**

- 10- and 20-inch lengths available in opaque; and 10-inch in clear
- Cap available with 0.75-, 1- or 1.5-inch NPT inlet and outlet ports
- Blue polypropylene caps available with optional pressure relief/bleed button on inlet side of cap

#### **SPECIFICATIONS**

| Model               | Big Blue®   | Big Clear   |
|---------------------|---|---|
| Housing             | Polypropylene   | Lexan® (#10)  |
| Сар                 | Polypropylene   | Polypropylene                                       |
| Button Assembly     | 300-Series Stainless Steel, EPDM, and Polypropylene   | 300-Series Stainless Steel, EPDM, and Polypropylene |
| 0-ring              | Buna-N®   | Buna-N®   |
| Maximum Temperature | 100°F (37.8°C)  | 100°F (37.8°C)                                      |
| Maximum Pressure    | #10 Big Blue <sup>°</sup> — 100 PSI (6.9 bar)<br>#20 Big Blue <sup>°</sup> — 90 PSI (6.2 bar) | #10 Big Clear — 100 PSI (6.9 bar)                   |

**CAUTION:** Protect against freezing to prevent cracking of the filter and water leakage.



The 150233, 150234, 150235, 150236, 150237, 150238, 150239, 150240, 150467, 150468, 150469, and 150470 Tested and Certified by NSF International to NSF/ANSI Standard 42 for material and structural integrity requirements.

**NOTE:** The Big Clear Series of housings are not NSF component listed.

## **HOUSING SPECIFICATIONS AND PERFORMANCE**

| Model         | Inlet/Outlet Size (in.) | Maximum Dimensions                | Initial ΔP (PSI) @ Flow Rate (gpm) |
|---------------|-------------------------|-----------------------------------|------------------------------------|
| #10 Big Blue® | .75                     | 13.125" x 7.25" (333 mm x 184 mm) | 2 PSI @ 15 gpm (0.1 bar @ 57 Lpm)  |
| #10 Big Blue® | 1                       | 13.125" x 7.25" (333 mm x 184 mm) | 1 PSI @ 15 gpm (0.1 bar @ 57 Lpm)  |
| #10 Big Blue® | 1.5                     | 13.625" x 7.25" (346 mm x 184 mm) | 1 PSI @ 20 gpm (0.1 bar @ 76 Lpm)  |
| #20 Big Blue® | .75                     | 23.375" x 7.25" (594 mm x 184 mm) | 2 PSI @ 15 gpm (0.1 bar @ 57 Lpm)  |
| #20 Big Blue® | 1                       | 23.375" x 7.25" (594 mm x 184 mm) | 1 PSI @ 15 gpm (0.1 bar @ 57 Lpm)  |
| #20 Big Blue® | 1.5                     | 23.875" x 7.25" (606 mm x 184 mm) | 1 PSI @ 20 gpm (0.1 bar @ 76 Lpm)  |
| #10 Big Clear | 1                       | 13.5" x 7.125" (343 mm x 181 mm)  | 1 PSI @ 15 gpm (0.1 bar @ 57 Lpm)  |
| #20 Big Clear | 1                       | 23.375" x 7.25" (594 mm x 184 mm) | 1 PSI @ 15 gpm (0.1 bar @ 57 Lpm)  |

<sup>\*</sup> Not performance tested or certified by NSF.

## **TEST DATA**

## Big Blue®/Big Clear Housing Water Flow Rate

